

# UNM STS 780-15-270 XDKC H842011

## Product Information Sheet



Technical data	H842011
Suction capacity	780 l/min
Eff. Delivery quantity	640 l/min
Start-up- / switch-off pressure	13/15 bar
Cylinder / Stages	2/2
Tank volume	270 l
Voltage	400 Volt/50 Hz
Drive power	5.5 kW
Speed	830 min <sup>-1</sup>
Noise	80 dB(A)
Dimensions (WxDxH)	1070 x 705 x 1875mm
Air outlet	¾"
Weight	278 kg

## Product Description

- Stationary compressor with star-delta switch with integral motor protection and low voltage circuit breaker which ensure a high degree of operating safety
- Compressor for work up to 15 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications:  
Expansion of compressed air systems,  
Increase reliability
- Highest quality of installed components
- With high performance cold dryer

# UNM STS 780-15-270 XDKC

## H842011

### Product Information Sheet



**Quiet running and optimal cooling**  
due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

**Reduced noise level**  
Less noise from new unit

**Compressor with low speed of rotation**  
Reduced vibrations preserve the compressor components

**Long service life**  
guaranteed by 15-year warranty against rust-through of vessel

**Space-saving design**  
Small footprints thanks to optimal arrangement of the components

**Attached cold dryer**  
For better air quality and work results

**Motionless standing position**  
Standard features include: anti vibration rubber feet

**Further information**

Complete equipment	Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start
Scope of delivery	Instruction manual
Warranty	- 12 months for professional industrial use - 24 months for private use only