UNM 410-10-50 W A713000

Product specification sheet





Technical Data	A713000
Air displacement	410 l/min
Max. free air delivery	295 l/min
Max. pressure	8/10 bar
Cylinder/Stage	2/1
Tank capacity	50 I
Voltage	230 Volt/50 Hz
Motor output	2,2 kW
Drive	1000 min ⁻¹
Noise level	96 dB(A)
Dimensions(WxDxH)	950x410x815 mm
Weight	64 kg

Product description

Fact Sheet

- Compressor is easily moveable due to castor wheels, ergonomic handle and extra handle on the tank
- · Mobile piston compressor with V-belt drive
- For applications up to 10 bar
- For private and mainly professional use
- · Equipped with filter pressure reducer
- Application: Using impact wrenches, ratchet screwdrivers, pneumatic screw drivers, saws, rivet guns, grease guns, staple and nail guns, paint spraying guns, cartridge guns, blow-out guns and air tyre inflators

UNM 410-10-50 W A713000

Product specification sheet



Easy transport

Ergonomic handle perfectly fitted and extra lifting handle on the tank

Precise working due to filter pressure reducer for controlling the air pressure perfectly

High flexibility

is provided by 2 m cable length

Convenient working

due to quick release coupling

Excellent working comfort thanks to clearly arranged pressure gauges for measuring tank and outlet pressure



Long service life

drive

thanks to the 10 years anti-corrosion warranty on the compressed air tank

Solid stand and comfort transportation due to large wheels and castor wheels with brakes

Further information	
Operates fully automatically	High quality Condor pressure switch with unloader valve, motor protection and on-off switch
Scope of delivery	Instruction manual
Warranty	12 months for industrial use 24 months for private (non-commercial) use 36 months when registrated online