UniMaster UNM 410-10-50 D A713010

Product specification sheet





Technical Data	A713010
Air displacement	410 l/min
Max. free air delivery	295 l/min
Max. pressure	10 bar
Cylinder/Stage	2/1
Tank capacity	50 I
Voltage	400 Volt/50 Hz
Motor output	2,2 kW
Drive	1000 min ⁻¹
Noise level	96 dB(A)
Dimensions(WxDxH)	410x950x875 mm
Weight	62 kg

Product description

Fact Sheet

- Compressor is easily moveable due to castor wheels, ergonomic handle and extra handle on the tank
- Mobile piston compressor with V-belt drive
- For applications up to 10 bar
- · For private and mainly professional use
- Equipped with filter pressure reducer
- Apllication: Using impact wrenchs, ratchet screwdrivers, saws, rivet guns, smaller sized staple and nail guns, spray pistols cartridge guns, grease guns, blow out guns and air tyre inflators

UniMaster UNM 410-10-50 D A713010

Product specification sheet



Silent run and perfect cooling

due to approved aggregate and ideal cooling air flow

High flexibility is provieded by 2 m cable length

Easy transport

Ergonomic handle perfectly fitted and extra lifting handle on the tank

Precise working

due to pressure reducing reculator for controlling the air pressure perfectly

Convenient working due to quick release

coupling

Excellent working comfort thanks to clearly
arranged pressure gauges
for measuring tank and
outlet pressure

Long service life thanks to the 10 years anti-corrosion warranty on the compressed air tankc

Solid stand and comfort transportation

due to large rubber wheels and caster wheels with brakes

Further information

Operates fully automatically	Unloader pressure switch, motor protection and on- off switch
Scope of delivery	Instruction manual
Warranty	12 months for industrial use 24 months for private (non-commercial) use 36 months when registrated online