

UNM 510-10-90 D A714000

Product specification sheet



Technical Data	A714000
Air displacement	510 l/min
Max. free air delivery	390 l/min
Max. pressure	10 bar
Cylinder/Stage	2/1
Tank capacity	90 l
Voltage	400 Volt/50 Hz
Motor output	3,0 kW
Drive	1240 min ⁻¹
Noise level	96 dB(A)
Dimensions(WxDxH)	1110x495x1000 mm
Weight	80 kg

Product description

Fact Sheet

- Compressor is easily moveable due to caster wheels and extra long handle
- Mobile piston compressor with V-belt drive
- For applications up to 10 bar
- High quality performing compressor is perfect for professional use
- Equipped with filter pressure reducer
- Application: Using impact wrenches, ratchet screwdrivers, pneumatic screw drivers, saws, rivet guns, grease guns, chipping hammers, smaller sized staple and nail guns, paint spraying guns, cartridge guns, blow-out guns and air tyre inflators

UNM 510-10-90 D A714000

Product specification sheet



Silent run and perfect cooling due to approved cooling air flow and approved aggregate with V-belt drive

Ergonomic extra long carrying handle perfectly fitted and extra lifting handle on the tank

Precise working due to filter pressure reducer for controlling the air pressure perfectly


High flexibility is provided by 2 m cable length

Convenient working due to quick release coupling

Long service life thanks to the 10 years anti-corrosion warranty on the compressed air tank

Excellent working comfort thanks to clearly arranged pressure gauges for measuring tank and outlet pressure

Solid stand and comfort transportation due to large rubber wheels and caster wheels with brakes



Further information

Operates fully automatically

Unloader pressure switch, motor protection and on-off switch

Scope of delivery

Instruction manual

Warranty

12 months for industrial use
24 months for private (non-commercial) use
36 months when registered online