UNM 510-10-90 DX A714001

Product specification sheet





Technical Data	A714001
Air displacement	510 l/min
Max. free air delivery	390 l/min
Max. pressure	10 bar
Cylinder/Stage	2/1
Tank capacity	90 I
Voltage	400 Volt/50 Hz
Motor output	3,0 kW
Drive	1240 min ⁻¹
Noise level	95 dB(A)
Dimensions(WxDxH)	1100x505x935mm
Weight	84,0 Kg

Product description

Fact Sheet

- Mobile piston compressor with V-belt drive
- For applications up to 10 bar
- This high quality performing air compressor is perfect for professional use
- Equipped with filter pressure reducer, oil-fog lubricator and condensate drain in operating height
- Application: Using impact wrenches, ratchet screwdrivers, pneumatic screw drivers, drills, grinders, saws, rivet guns, grease guns, needle scalers, chipping hammers, smaller sized staple and nail guns, paint spraying guns, shot blasting guns, cartridge guns, blow-out guns and air tyre inflators

UNM 510-10-90 DX A714001

Product specification sheet



Silent run and perfect cooling due to approved aggregate with V-belt drive and ideal cooling air flow

Perfect working conditions thanks to clearly arranged control panel with filter pressure reducer, oilfog lubricator and shutoff ball valve on the discharge port

Working safely due to **two** quick release couplings

Working

comfortibly with perfect overview two pressure
gauges for
measuring tank and
outlet pressure are
placed perfectly

Ergonomic carrying handle perfectly fitted and extra lifting handle on the tank

High flexibility is provided by **4 m** cable lenght

Long service life thanks to the 15 years anti-corrosion warranty on the compressed air tank

Solid stand and safe transport due to caster wheels and large soft rubber tyres providing optimal puncture protection

Further information

Operates fully automatically	Unloader pressure switch, motor protection and on- off switch
Scope of delivery	Instruction manual
Warranty	12 months for industrial use 24 months for private (non-commercial) use 36 months when registrated online