

UNM 660-10-90 DX A715001

Product specification sheet



Technical Data	A715001
Air displacement	660 l/min
Max. free air delivery	520 l/min
Max. pressure	10 bar
Cylinder/Stage	2/2
Tank capacity	90 l
Voltage	400 Volt/50 Hz
Motor output	4,0 kW
Drive	1000 min ⁻¹
Noise level	97dB(A)
Dimensions(WxDxH)	1100x 505x1000mm
Weight	106 kg

Product description

Fact Sheet

- Mobile piston compressor with V-belt drive
- For applications up to 10 bar
- High quality performing compressor is perfect for professional use
- Equipped with filter pressure reducer, oil-fog lubricator and condensate drain in operating height
- Application: Using impact wrenches, ratchet screwdrivers, pneumatic screw drivers, drills, grinders, saws, rivet guns, grease guns, needle scalars, chipping hammers, smaller sized staple and nail guns, paint spraying guns, shot blasting guns, cartridge guns, blow-out guns and air tyre inflators

UNM 660-10-90 DX A715001

Product specification sheet



Ergonomic telescopic handle perfectly fitted and extra lifting handle on the tank

Silent run and perfect cooling due to approved cooling air flow and approved aggregate with V-belt drive

Perfect working conditions thanks to clearly arranged control panel with filter pressure reducer, oil-fog lubricator and **shutoff ball valve on the discharge port**

High flexibility is provided by **4 m** cable length

Working safely due to **2 quick release couplings**

Working comfortably with perfect overview - two pressure gauges for measuring tank and outlet pressure

Long service life thanks to the **15 years** anti-corrosion warranty on the compressed air tank

Solid stand and comfort transportation due to castor wheels and large, **indestructible rubber wheels**

Further information

Operates fully automatically

Unloader pressure switch, motor protection and on-off switch

Scope of delivery

Instruction manual

Warranty

12 months for industrial use
24 months for private (non-commercial) use
36 months when registered online