

Tyre pressure gauge RF-RM calibrated

Product Information Sheet



Technical data	D004017
Base unit number	T460069
Pressure gauge display	0 - 10 bar
Maximal pressure	10 bar
Operating temperature range	-20 - + 60 °C
Hose length	0.4 m
Valve connector type	Straight plug-in valve
Dimensions (without hose) (WxDxH)	145 x 50 x 235 mm
Weight	0.36 kg
Date	15.07.2013

Product Description

Fact Sheet

- **USE**
The calibrated tyre pressure gauge is suitable for easy inflating and emptying of passenger cars and motorcycles tyres, up to a tyre pressure of 10 bar.
- **CALIBRATED GAUGE**
The calibrated version offers maximum security on the accuracy of tyre air pressure.
- **GAUGE WITH RUBBER COVER**
The rubber cover offers large degree of protection against hits.
- **REQUIRED AIRQUALITY**
Cleaned free of oil and condensate

Tyre pressure gauge RF-RM calibrated

Product Information Sheet



Optimised readability

- Pressure gauge display 0 - 10 bar

Protected pressure gauge

- The rubber cover offers large degree of protection against hits.

Flexible

- 0.4 m long hose allows flexible working

Easy handling

- Easy handling thanks to separated buttons



Straight plug-in valve

Calibrated

- Calibration approval (quarter and year) is shown on the pressure gauge and on the handle
- It is valid in Germany for 2 years from production date on

Further information

Scope of delivery

Instruction manual, hose, valve connector, tyre pressure gauge

Warranty

12 months for professional industrial use
24 months for private use only