

2-in-1 Air Nailer/Stapler KNG 40 / 50 SYS D300046



Product specification sheet



Technical Data	D300046
Trip mechanism	Single shot with contact safety mechanism
Air consumption per shot	1,1 l per shot
Type of staplers	Type 90
Length of staplers	13-40 mm
Crown width	5,7 mm
Type of brad nails	SN
Length of brad nails	16-50 mm
Magazine capacity (number of staplers)	100
Operating pressure	5-8 bar
Vibration value	2,45 m/s ²
Sound pressure level (LPA)	82 dB (A)
Sound power level (LWA)	95 dB (A)
Dimensions (WxDxH)	248x67x257 mm
Weight	1,16 kg

Product description

Fact Sheet

- Users: Carpenters, interior designers, trade fair constructors
- Perfect for mounting of tongue and groove panels, wood ceilings, skirting boards and cornice panels, chip boards, furniture back panels and panelling
- Depth adjustment sets stapler to desired depths conveniently
- Extra light and handy housing

2-in-1 Air Nailer/Stapler KNG 40 / 50 SYS D300046



Product specification sheet

Adjustable exhaust port directs exhaust away from the operator and keeps your workpiece clean

Rubber grip absorbs shock and vibration and insulates against cold

Lighter and compact stapler which is less tiring to use if a large amount of stapling is required

Depth adjustment sets stapler to desired depths conveniently



Easy, tool-less opening of the magazines' front plate for clearing obstructions

Contact safety mechanism helps prevent accidental firing

Further information

Scope of delivery

Delivered in Systainer with 1000 brad nails (length: 40 mm), 2000 staplers Type 90 (length: 30 mm), hex wrench, goggles, lubricant oil and instruction manual

Warranty

36 months when registered online
24 months for private (non-commercial) use
12 months for industrial use