

Automatic hose rewriter

D312516/ SLA-8-9

Product Information Sheet



Technical data	D312516
Base unit number	T480014
Max. operating pressure	15 bar at 20°C
Length air hose	9 m
Length inlet air hose	2 m
Exterior diameter	12 mm
Interior diameter	8 mm
Ambient temperature range	-5°C - +40°C
Dimensions (WxDxH)	380x102x285 mm
Weight	5,0 kg
Date	25.01.2012 / mlor

Product Description

- Fact Sheet
- Well equipped and ready to use: quick release coupling with plastic protection and long connecting hose (2m) with plug nipple
 - Impact-resistant and robust metal housing protects the air hose against dirt and other external influences
 - Elastic air hose with woven fabric inlay is highly resistant against abrasion
 - Retaining bracket is easily adjustable at will
 - EC-Declaration of conformity according to 2006/42/EG, DIN EN ISO 12100-1 and DIN EN ISO 12100-2

Automatic hose rewriter D312516/ SLA-8-9

Product Information Sheet



Well equipped and ready to use:
quick release coupling and long
connecting hose (2m) with plug nipple

Fatigue-free work
due to hose locking
device every 10-30
cm and swiveling U-
bracket (190°)

Various application
options due to possible
mounting on wall and
ceiling



**No reworking and
imperfection**
plastic protection avoids
scratches on surfaces

High flexibility
in installing and working
with hose rewriter due to
long inlet air hose (2m)

Long durability
because of highly resistant,
elastic air hose with woven
fabric inlay and anti-kink
device

Further information

Scope of delivery	Hose rewriter with swivelling U-bracket, quick release coupling, plug nipple and instruction manual
Warranty	24 months for private use only 12 months for professional industrial use