

# UNM 240-8-40 W Clean H332000

Product specification sheet



Technical Data	H332000
Air displacement	240 l/min
Max. free air delivery <sup>1)</sup>	170 l/min
Max. pressure	6/8 bar
Tank capacity	40 l
Voltage	230 Volt/50 Hz
Motor output	1,5 kW
Drive	1450 min <sup>-1</sup>
Noise level <sup>2)</sup>	66 dB(A)
Dimensions(WxDxH)	600 x 410 x 770 mm
Weight	46 Kg
Number of dental units	3

1) Max. free air delivery at 5 bar 2) LpA1 sound pressure level in accordance with DIN EN ISO 2151

# UNM 240-8-40 W Clean H332000

Product specification sheet



## Oil free and clean

Premium oil free compressor with PTFE-coated pistons. No oil particles in compressed air and condensate.

## Very good running behaviour

An optimal air flow provides excellent cooling and outstanding low operating temperatures. This enables a high duty cycle up to 80%.

## Close monitoring of the effective running time

The mechanical operating hours counter provides a precise analysis for maintenance and service.

**Precise function** due to pressure regulator for controlling the air pressure perfectly. Filter pressure regulator removes moisture from the oil free air.

## Ready to use

All models are ready to be connected upon delivery.



## Absolutely reliable

Low speed and premium components ensure a long lifetime.

## Extremely low-noise

Low noise level and und minimal vibrations due to a decoupled compressor unit.

**15 years anti-corrosion warranty** on the compressed air tank due to inner powder coating

**Certified as a medical product**  
in accordance with 93/42/EWG.