

UNM 720-8-90 D Clean H362000

Product specification sheet



Technical Data	H362000
Air displacement	720 l/min
Max. free air delivery ¹⁾	500 l/min
Max. pressure	6/8 bar
Tank capacity	90 l
Voltage	400 Volt/50 Hz
Motor output	2x 2,2 kW
Drive	1450 min ⁻¹
Noise level ²⁾	69 dB(A)
Dimensions(WxDxH)	1100 x 600 x 820 mm
Weight	113 Kg
Number of dental units	8

1) Max. free air delivery at 5 bar 2) LpA1 sound pressure level in accordance with DIN EN ISO 2151

UNM 720-8-90 D Clean H362000

Product specification sheet



Oil free and clean


Premium oil free compressor with PTFE-coated pistons. No oil particles in compressed air and condensate.

Very good running behaviour

An optimal air flow provides excellent cooling and outstanding low operating temperatures. This enables a high duty cycle up to 80%.

Close monitoring of the effective running time

The two mechanical operating hours counters provide a precise analysis for maintenance and service.



Absolutely reliable

Low speed and premium components ensure a long lifetime.

Precise function due to pressure regulator for controlling the air pressure perfectly. Filter pressure regulator removes moisture from the oil free air.

Extremely low-noise

Low noise level and und minimal vibrations due to decoupled compressor units.

Ready to use

All models are ready to be connected upon delivery.

15 years anti-corrosion warranty on the compressed air tank due to inner powder coating

Certified as a medical product
in accordance with 93/42/EWG.