

UNM STS 660-10-90 XS H811100

Product Information Sheet



Technical Data	H811100
Suction capacity	660 l/min
Eff. Delivery quantity	520 l/min
Start-up- / switch-off pressure	8/10 bar
Cylinder / Stages	2/2
Tank volume	90 l
Voltage	400 Volt/50 Hz
Drive power	4.0 kW
Speed	1025 min ⁻¹
Noise	69 dB(A)
Dimensions (WxDxH)	775 x 740 x 1275 mm
Air outlet	¾"i
Weight	162 kg
Date	02.03.2011 / afal

Product Description

- Sound-insulated stationary compressor for work up to 10 bar
- Set up in sensitive areas possible because compressor is fitted with a sound absorption hood
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Standard features include: all fittings and rubber vibration elements
- Easily accessible condensate trap under the vessel

UNM STS 660-10-90 XS H811100

Product Information Sheet



Increased output and high efficiency

Due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

Low speed of rotation

Reduces vibrations, preserves components and reduces noise level

Motionless standing position

Standard features include: anti vibration rubber feet

Perfectly soundproofed

Due to sound absorption hood extremely quiet

Reduced noise level

Set up in sensitive areas possible

Long service life

Guaranteed by 15-year warranty against rust-through of vessel

Easily accessible condensate trap

Also simple connection of an Ecomat condensate discharger



Further information

Complete equipment

Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start

Scope of delivery

Instruction manual

Warranty

- 12 months for professional industrial use
- 24 months for private use only