

UNM STS 660-10-270 XDK H812010

Product Information Sheet



Technical data	H812010
Suction capacity	660 l/min
Eff. Delivery quantity	520 l/min
Start-up- / switch-off pressure	8/10 bar
Cylinder / Stages	2/2
Tank volume	270 l
Voltage	400 Volt/50 Hz
Drive power	4.0 kW
Speed	1025 min ⁻¹
Noise	78 dB(A)
Dimensions (WxDxH)	945 x 705 x 1800mm
Air outlet	¾"
Weight	206 kg

Product Description

- Stationary compressor
- Compressor for work up to 10 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications:
Expansion of compressed air systems,
Increase reliability
- Highest quality of installed components
- With high performance cold dryer

UNM STS 660-10-270 XDK H812010

Product Information Sheet



Quiet running and optimal cooling
due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

Reduced noise level
Less noise from new unit

Compressor with low speed of rotation
Reduced vibrations preserve the compressor components

Attached cold dryer
For better air quality and work results

Long service life
guaranteed by 15-year warranty against rust-through of vessel

Space-saving design
Small footprints thanks to optimal arrangement of the components

Motionless standing position
Standard features include: anti vibration rubber feet

Further information

Complete equipment	Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start
Scope of delivery	Instruction manual
Warranty	- 12 months for professional industrial use - 24 months for private use only