

# UNM STS 580-15-270 XS H822100

## Product Information Sheet



| Technical Data         | H822100               |
|------------------------|-----------------------|
| Suction capacity       | 580 l/min             |
| Eff. Delivery quantity | 470 l/min             |
| Pressure               | 15 bar                |
| Cylinder / Stages      | 2/2                   |
| Tank volume            | 270 l                 |
| Voltage                | 400 Volt/50 Hz        |
| Drive power            | 4.0 kW                |
| Speed                  | 915 min <sup>-1</sup> |
| Noise                  | 69 dB(A)              |
| Dimensions (WxDxH)     | 775 x 740 x 1905 mm   |
| Air outlet             | ¾"i                   |
| Weight                 | 216 kg                |
| Date                   | 02.03.2011 / afal     |

## Product Description

- Sound-insulated stationary compressor for work up to 15 bar
- Set up in sensitive areas possible because compressor is fitted with a sound absorption hood
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Standard features include: all fittings and rubber vibration elements
- Easily accessible condensate trap under the vessel

# UNM STS 580-15-270 XS H822100

## Product Information Sheet



### Increased output and high efficiency

Due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

### Perfectly soundproofed

Due to sound absorption hood extremely quiet

### Low seed of rotation

Reduces vibrations, preserves components and reduces noise level

### Reduced noise level

Set up in sensitive areas possible

### Long service life

Guaranteed by 15-year warranty against rust-through of vessel

### Motionless standing position

Standard features include: anti vibration rubber feet

### Easily accessible condensate trap

Also simple connection of an Ecomat condensate discharger



## Further information

Complete equipment

Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start

Scope of delivery

Instruction manual

Warranty

- 12 months for professional industrial use  
- 24 months for private use only