# UNM STS 1000-10-500 XDK 1121580503 (No. old: H833010)

**Product Information Sheet** 





Technical data	1121580503
Suction capacity	1000 l/min
Eff. Delivery quantity	790 I/min
Start-up- / switch-off pressure	8/10 bar
Cylinder / Stages	2/2
Tank volume	500 I
Voltage	400 Volt/50 Hz
Drive power	5.5 kW
Speed	1260 min <sup>-1</sup>
Noise	82 dB(A)
Dimensions (WxDxH)	1145 x 850 x 2020mm
Air outlet	3/4"
Weight	316 kg

### **Product Description**

- Stationary compressor
- Compressor for work up to 10 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications: Expansion of compressed air systems, Increase reliability
- Highest quality of installed components
- With high performance cold dryer

# UNM STS 1000-10-500 XDK 1121580503 (No. old: H833010)

**Product Information Sheet** 



#### Quiet running and optimal cooling

due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

Compressor with

low speed of rotation

Reduced vibrations preserve the compressor components

Long service life

guaranteed by 15-year warranty against rust-through of vessel

Space-saving design

Small footprints thanks to optimal arrangement of the components

Reduced noise level

Less noise from new unit

Attached cold dryer

For better air quality and work results

Motionless standing position

Standard features include: anti vibration rubber feet

#### **Further information**

Complete equipment	Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start
Scope of delivery	Instruction manual
Warranty	<ul><li>12 months for professional industrial use</li><li>24 months for private use only</li></ul>