UNM STS 780-15-500 XDK 1121580504 (No. old: H843010)

Product Information Sheet





Technical data	1121580504
Suction capacity	780 l/min
Eff. Delivery quantity	640 l/min
Start-up- / switch-off pressure	13/15 bar
Cylinder / Stages	2/2
Tank volume	500 I
Voltage	400 Volt/50 Hz
Drive power	5.5 kW
Speed	980 min ⁻¹
Noise	80 dB(A)
Dimensions (WxDxH)	1145 x 850 x 2020mm
Air outlet	3/4"
Weight	331 kg

Product Description

- Stationary compressor
- Compressor for work up to 15 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications: Expansion of compressed air systems, Increase reliability
- Highest quality of installed components
- With high performance cold dryer


UNM STS 780-15-500 XDK 1121580504 (No. old: H843010)

Product Information Sheet



Quiet running and optimal cooling

due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery



Compressor with low speed of rotation -

Reduced vibrations preserve the compressor components

Long service life

guaranteed by 15-year warranty against rust-through of vessel



Small footprints thanks to optimal arrangement of the components

Reduced noise level

Less noise from new unit

Attached cold dryer For better air quality

and work results

Motionless standing position

Standard features include: anti vibration rubber feet

Further information

Complete equipment	Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start
Scope of delivery	Instruction manual
Warranty	12 months for professional industrial use24 months for private use only