UNM STS 1250-10-270 XDK H852010

Product Information Sheet





Technical data	H852010
Suction capacity	1250 l/min
Eff. Delivery quantity	980 l/min
Start-up- / switch-off pressure	8/10 bar
Cylinder / Stages	2/2
Tank volume	270 l
Voltage	400 Volt/50 Hz
Drive power	7.5 kW
Speed	1240 min ⁻¹
Noise	84 dB(A)
Dimensions (WxDxH)	1070 x 705 x 1875mm
Air outlet	3/4"
Weight	283 kg

Product Description

- Stationary compressor
- · Compressor for work up to 10 bar
- Smooth running belt driven 2-cylinder unit with 2-stage compression
- Suitable for many jobs in the professional field
- Applications: Expansion of compressed air systems, Increase reliability
- · Highest quality of installed components
- With high performance cold dryer

UNM STS 1250-10-270 XDK H852010

Product Information Sheet



Quiet running and optimal cooling

due to the new wedge-driven compressor unit with optimal cooling air flow and improved delivery performance

Reduced noise level

Less noise from new unit

Compressor with low speed of rotation

Reduced vibrations preserve the compressor components

Attached cold dryer

For better air quality and work results

Long service life

guaranteed by 15-year warranty against rust-through of vessel

Space-saving design

Small footprints thanks to optimal arrangement of the components

Motionless standing position

Standard features include: anti vibration rubber feet

Further information

Complete equipment	Pressure switch, motor protection, safety and check valve, container pressure gauge, unloaded start
Scope of delivery	Instruction manual
Warranty	12 months for professional industrial use24 months for private use only